

# ODE-3-240058-3042

## Optidrive E3 VFD Datasheet

**2.2 kW (3 HP). 5.8 A. 380-480 V. 3PH**

Variadores de frecuencia



### Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	7.5 A
Supply Fuse or MCB (Type B)	16 A

### Output Ratings

Motor Output Rating	2.2 kW (3 HP)
Output Voltage	0 – Supply Voltage
Output Current	5.8 A

### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

### Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	


### Dimensions

Size	2
Height	221 mm (8.7 in)
Width	110 mm (4.33 in)
Depth	150 mm (5.91 in)
Weight	1.7 kg (3.75 lbs)
Fixings	4 x M5

### Packaged Dimensions

Height	234 mm (9.21 in)
Width	144 mm (5.67 in)
Depth	260 mm (10.24 in)
Weight	1.9 kg (4.19 lbs)



 **Buy this drive or get more information**  
Find your local sales partner on  
[inverterkdrives.com](http://inverterkdrives.com)

