

ODE-3-240095-3042

Optidrive E3 VFD Datasheet

4 kW (5 HP). 9.5 A. 380-480 V. 3PH

Variadores de frecuencia



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	11.5 A
Supply Fuse or MCB (Type B)	16 A

Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	9.5 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	

Dimensions

Size	2
Height	221 mm (8.7 in)
Width	110 mm (4.33 in)
Depth	150 mm (5.91 in)
Weight	1.7 kg (3.75 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	234 mm (9.21 in)
Width	144 mm (5.67 in)
Depth	260 mm (10.24 in)
Weight	1.9 kg (4.19 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

