

ODE-3-340140-3042

Optidrive E3 VFD Datasheet

5.5 kW (7.5 HP). 14 A. 380-480 V. 3PH

Variadores de frecuencia



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	17.2 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	5.5 kW (7.5 HP)
Output Voltage	0 – Supply Voltage
Output Current	14 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	

Dimensions

Size	3
Height	261 mm (10.28 in)
Width	131 mm (5.16 in)
Depth	175 mm (6.89 in)
Weight	3.2 kg (7.05 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	254 mm (10 in)
Width	162 mm (6.38 in)
Depth	315 mm (12.4 in)
Weight	3.5 kg (7.72 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

